

MOBIELE AFZUIGINGEN

Vergelijk



GENERAL INFORMATION

	Dufil mini	Tofil mono	Tofil PRO - 1 Arm	Tofil PRO - 2 Arms	Tofil PULSE - 1 Arms	Tofil PULSE - 2 Arms
Filter Type	Disposable	Cartridge	Cartridge	Cartridge	Cartridge	Cartridge
Filter Media						
<i>Standard</i>	G4 + M5 + H13 HEPA	nanoBLEND FR	nanoBLEND FR	nanoBLEND FR	nanoBLEND FR	nanoBLEND FR
<i>Optional</i>	Activated Carbon	polyMIGHT PTFE 65	polyMIGHT PTFE 65	polyMIGHT PTFE €	polyMIGHT PTFE 65	polyMIGHT PTFE 65
No of Filter Stage	3	2	2	2	2	2
No of Filter Set	1	1	1	1	2	2
Total Filtration Area						
<i>Standard</i>	15 m ²	18 m ²	24 m ²	24 m ²	36 m ²	36 m ²
<i>Optional</i>	15 m ²	10 m ²	20 m ²	20 m ²	20 m ²	20 m ²
Filtration Efficiency						
<i>Standard</i>	H13 Class	F9 Class	F9 Class	F9 Class	F9 Class	F9 Class
<i>Optional</i>	H13 Class	H13/H14 Class	H13/H14 Class	H13/H14 Class	H13/H14 Class	H13/H14 Class
TECHNICAL INFORMATION						
Extraction Capacity	900 m ³ /h	1.200 m ³ /h	1.400 m ³ /h	1.100 m ³ /h x 2	1.400 m ³ /h	1.100 m ³ /h x 2
Dimensions (W x L x H)	700 x 600 x 1.100 mm	660 x 805 x 1.210 mm	650 x 815 x 1.320 mm	650 x 815 x 1.320 mm	890 x 810 x 1.760 mm	890 x 810 x 1.760 mm
Motor	1,1 kW - 3.000 rpm	0,75 kW - 3.000 rpm	1,1 kW - 3.000 rpm	1,1 kW - 3.000 rpm	1,1 kW - 3.000 rpm	1,1 kW - 3.000 rpm
Power Supply						
<i>Standard</i>	230 V / 50 Hz	380 V / 50 Hz	380 V / 50 Hz	380 V / 50 Hz	380 V / 50 Hz	380 V / 50 Hz
<i>Optional</i>	110 V / 50 Hz	230 V 110 V - 50 Hz	460 V / 60 Hz	460 V / 60 Hz	460 V / 60 Hz	460 V / 60 Hz
Noise Level	72 dB(a)	72 dB(a)	72 dB(a)	72 dB(a)	73 dB	73 dB(a)