PERLITE

Feature: Cleanable

APPLICATIONS

■ Food and beverage industry, pharmaceutical industry, chemical industry, paint and coating industry, industrial companies, waste water treatment, swimming pool water, waste disposal and solvent recovery.

FEATURE

- High filter capacity.
- High brightness.
- High flow rate.
- Atmospheric material, no crystal particles or asbestos particles.
- Low density compared to other materials.
- Easy removal of the filter cake.
- Colour: white and off-white.
- Uniform precoating.
- Sterile product PH value 6.5–7.5.
- Dioxin and PCBs: test figures show that values are significantly below current and proposed standards in accordance with European Directive 2002/32/EU.



| TYPE | RELATIVE CURRENT | DENSITY G/LITER WET FILTER CLOTH | PARTICLE SIZE MEDIUM μ | PERMEABILITY OF THE PRODUCT | FLOATERS |
|------|---------------------|-------------------------------------|---------------------------|-----------------------------|----------|
| 10 | 20 | 130-150 | 50 μ | 11 darcy | 7-15% |
| 30SP | 15 | 140-160 | 40 μ | 9 darcy | 4-8% |
| 30 | 10 | 140-160 | 25 μ | 5-6 darcy | 3-12% |
| 50 | 7,5 | 150-170 | 19 μ | 2-3,5 darcy | 3-12% |
| 50S | 6 | 150-170 | 18 μ | 1,8-1,5 darcy | 3-12% |
| 60 | 5 | 150-220 | 17 μ | 1,6-1,4 darcy | 3-7% |
| 80 | 3,8 | 180-220 | 15 μ | 1-0,8 darcy | 3-5% |
| 100 | 3 | 180-210 | 13 μ | 0,7 darcy | 1-4% |
| 150 | 2 | 200-270 | 10 μ | 0,6 darcy | 1-2% |
| 180 | 1 | 210-300 | 7 μ | 0,4 darcy | <1% |

