

# CUBE PAINT FILTERBOX

Cardboard cubes for capturing paint spray

## ADVANTAGES

- Quick and easy to change
- Extended filtration process thanks to labyrinth layout
- V-shaped filter contributes to more effective paint mist capture
- Filter is easily unfolded and can be installed immediately

## APPLICATIONS

- Spray booths, painting lines, coating

## SPECIFICATIONS

- Recommended air flow: 1,800 - 3,500 m<sup>3</sup>/m<sup>2</sup>h
- Differential pressure: 72 Pa (300mm) 91 Pa (500mm)
- Max. temperature: 85 °C
- Collection capacity: 80 kg/m<sup>2</sup> (300mm) 120 kg/m<sup>2</sup> (500mm)
- Separation efficiency: Up to 98%
- The filter boxes are available with or without seal



DESCRIPTION	WIDTH MM	HEIGHT MM	DEPTH MM	MAX. CAPACITY M <sup>3</sup> /H	ΔP INITIAL	MAX. SEPARATION EFFICIENCY	MAX. DUST LOADCAPACITY
<b>Cube Paint filter 300</b>	500	500	300	1800	72	98%	20 kg/box
<b>Cube Paint filter 500</b>	500	500	500	3500	91	98%	30 kg/box

Specifications may differ depending on the type of paint.

**Cube Paint filter 300**



**Cube Paint filter 500**

