

# SS SERIES SEPARATOR ELEMENT

Feature: Cleanable

Page: 1 of 2

## APPLICATIONS

- Condensate of hydrocarbons, diesel, kerosene, LPG, lubricants and aromatics.

## FEATURES

- Tested and qualified according to the 5th edition of EL 1581.
- Hydrophobic, synthetic filter medium.
- Superior water-repellent properties by Teflon® and paper.
- Cleanable and reusable.
- Recommended working temperature 115 °C.
- pH range from 5 to 9.
- Flow direction: from inside to outside.



MODEL NUMBER	OUTSIDE DIAMETER		NOMINAL INCHES	LENGTH MM	INSIDE DIAMETER SEAL		INNERDIAMETER ASSEMBLY END	
	INCHES	MM			INCHES	MM	INCHES	MM
<b>SS318FA</b>	3	76	18	460	17/32	13	2	51
<b>SS324FA</b>	3	76	24	610	17/32	13	2	51
<b>SS330FA</b>	3	76	30	760	17/32	13	2	51
<b>SS412FC</b>	4 1/8	105	11 1/2	290	17 1/8	48	17 1/8	48
<b>SS422FC</b>	4 1/8	105	22 1/2	570	17 1/8	48	17 1/8	48
<b>SS432FC</b>	4 1/8	105	31 1/2	800	17 1/8	48	17 1/8	48
<b>SS417B</b>	4 1/2	114	17	430	17/32	13	3 1/2	89
<b>SS430FB</b>	4 1/2	114	24	610	17/32	13	3 1/2	89
<b>SS436FB</b>	4 1/2	114	30	760	17/32	13	3 1/2	89
<b>SS609GB</b>	4 1/2	114	36	910	17/32	13	3 1/2	89
<b>SS609FF</b>	6	152	9	230	17/32	13	3 1/2	89
<b>SS611FD</b>	6	152	9	230	17/32	13	4 1/2	114
<b>SS612FB</b>	6	152	11 1/4	290	3 1/2	48	3 1/2	89
<b>SS614FD</b>	6	152	12	300	17/32	13	3 1/2	89
<b>SS616FD</b>	6	152	14 1/2	370	3 1/2	48	3 1/2	89
<b>SS618FB</b>	6	152	16 1/4	410	3 1/2	48	3 1/2	89
<b>SS623FD</b>	6	152	18	460	17/32	13	3 1/2	89
<b>SS624FB</b>	6	152	22 1/4	560	3 1/2	48	3 1/2	89
<b>SS624FE</b>	6	152	24	610	17/32	13	3 1/2	89
<b>SS624FF</b>	6	152	24	610	17/32	13	4 1/2	105
<b>SS629FD</b>	6	152	24	610	17/32	13	4 1/2	114
<b>SS630FE</b>	6	152	29	740	3 1/2	48	3 1/2	89
<b>SS633FD</b>	6	152	30	760	17/32	13	4 1/4	105

# SS SERIE SEPARATOR ELEMENT

Feature: Cleanable

Page: 2 of 2

MODEL NUMBER	OUTSIDE INCHES	DIAMETER MM	NOMINAL INCHES	LENGTH MM	INSIDE DIAMETER SEAL END		INNER DIAMETER ASSEMBLY END	
					INCHES	MM	INCHES	MM
<b>SS636FD</b>	6	152	33	840	3 1/2	48	3 1/2	89
<b>SS636FE</b>	6	152	36	910	3 1/2	48	3 1/2	89
<b>SS636FF</b>	6	152	36	910	17/32	13	4 1/8	105
<b>SS640FD</b>	6	152	36	910	17/32	13	4 1/2	114
<b>SS640FE</b>	6	152	40	1020	3 1/2	48	3 1/2	89
<b>SS644FD</b>	6	152	40	1020	17/32	13	4 1/8	105
<b>SS644FE</b>	6	152	44	1120	3 1/2	48	3 1/2	89
<b>SS644FF</b>	6	152	44	1120	17/32	13	4 1/8	105
<b>SS648FE</b>	6	152	44	1120	17/32	13	4 1/2	114
<b>SS648FF</b>	6	152	48	1220	17/32	13	4 1/8	105
<b>SS656FF</b>	6	152	56	1420	17/32	13	4 1/2	114