

HEPA MEDIUM CAP

Absolute filters with MDF frame and flat filter pack, filter class E10-H14

APPLICATIONS

- Final filter stage in air handling units for cleanrooms
- Filtration of harmful and toxic particles

BENEFITS

- Individual leak test at 0.3µ at 0.45 m/s according to DIN24 184 standard
- Individual MPPS scan at 0.12 µ at 0.45 m/s according to EN1822 standard
- Individual scan report provided with each filter

SPECIFICATIONS

- Medium: Minipleated fiberglass paper
- Frame: MDF, also available with steel or aluminum frame
- Sealing: Polyurethane
- Spacers: Continuous cord in thermoplastic
- Gasket: Semi-circular monobloc polyurethane
- Recommended final resistance: 600Pa
- Max. continuous temperature: 70°C
- Max. relative humidity: 90%



DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	DEPTH (C) MM	CLASS EN1822	FLOW RATE M3/U	ΔP INITIAL
EPA E10 610x610x292 M MC	610	610	292	E10	4400	250
EPA E10 305x610x292 M MC	305	610	292	E10	2200	250
EPA E10 305x305x292 M MC	305	305	292	E10	1100	250
HEPA H13 610x610x292 M MC	610	610	292	H13	2500	250
HEPA H13 305x610x292 M MC	625	610	292	H13	1225	250
HEPA H13 305x305x292 M MC	305	305	292	H13	615	250
HEPA H14 610x610x292 M MC	610	610	292	H14	2260	250
HEPA H14 305x610x292 M MC	305	610	292	H14	1130	250
HEPA H14 305x305x292 M MC	305	305	292	H14	565	250

Custom sizes on request.