

RPV85 ES, RPV95 ES AND RPV98 ES

Compact filters in V-form, low energy, filter coarse ISO ePM1-60%, ISO ePM1-70%, ISO ePM1-80%

APPLICATIONS

- Filtration for air handling units equipped with a pre-filter
- Pre-filter for Cleanroom application

ADVANTAGES

- Large filter surface
- High filter efficiency
- Eurovent certified through the manufacturer Deltrian

CHARACTERISTICS

- Medium: Minipleated glass fiber paper
- Frame: Polystyrene plastic
- Seal: Polyurethane
- Spacers: Hot-melt cord
- Recommended final pressure drop: 250Pa
- Max. continuous temperature: 70°C
- Max. relative humidity: 100%



ITEM NO.	DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	THICKNESS (C) MM	ISO COARSE 16890	CLASS EN 779:2012	FLOW M3/U	ΔP INITIAL	KWH/J 4/21-2018
25094	RPV85 ES 592x592x292	592	592	292	ePM1-60%	F7	3400	68	836
25095	RPV85 ES 288x592x292	288	592	292	ePM1-60%	F7	1700	68	836
25096	RPV85 ES 490x592x292	490	592	292	ePM1-60%	F7	2850	68	836
26300	RPV95 ES 592x592x292	592	592	292	ePM1-70%	F8	3400	83	1058
26301	RPV95 ES 288x592x292	288	592	292	ePM1-70%	F8	1700	83	1058
26302	RPV95 ES 490x592x292	490	592	292	ePM1-70%	F8	2850	83	1058
26304	RPV98 ES 592x592x292	592	592	292	ePM1-80%	F9	3400	92	1170
26305	RPV98 ES 288x592x292	288	592	292	ePM1-80%	F9	1700	92	1170
26311	RPV98 ES 490x592x292	490	592	292	ePM1-80%	F9	2850	92	1170