

RPV65, RPV85, RPV95 EN RPV98

Compactfilters in V-vorm,
filter coarse ISO ePM10-70% - ISO ePM1-80%



APPLICATIONS

- Filtration for air handling units equipped with a pre-filter
- Pre-filter for Cleanroom application

BENEFITS

- Compact and affordable
- Large filter surface
- High filter efficiency
- Available in a bacteria- and fungus-resistant version
- Eurovent certified

SPECIFICATIONS

- Medium: Minipleated glass fiber paper
- Frame: Polystyrene plastic
- Seal: Polyurethane
- Spacers: Hot-melt cord
- Recommended final pressure drop: 250Pa
- Max. continuous temperature: 70°C
- Max. relative humidity: 100%



DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	LENGTH (C) MM	ISO COARSE 16890	CLASS EN 779:2012	FLOW RATE m³/U	ΔP INITIAL	KWH/J 4/21-2018	ENERGY CLASS
RPV65 592x592x292	592	592	292	ePM10-70%	M6	3400	56	889	C
RPV65 288x592x292	288	592	292	ePM10-70%	M6	1700	56	889	
RPV65 490x592x292	490	592	292	ePM10-70%	M6	2850	56	889	
RPV85 592x592x292	592	592	292	ePM1-60%	F7	3400	88	1433	C
RPV85 288x592x292	288	592	292	ePM1-60%	F7	1700	88	1433	
RPV85 490x592x292	490	592	292	ePM1-60%	F7	2850	88	1433	
RPV95 592x592x292	592	592	292	ePM1-75%	F8	3400	108	1572	D
RPV95 288x592x292	288	592	292	ePM1-75%	F8	1700	108	1572	
RPV95 490x592x292	490	592	292	ePM1-75%	F8	2850	108	1572	
RPV98 592x592x292	592	592	292	ePM1-80%	F9	3400	129	1751	C
RPV98 288x592x292	288	592	292	ePM1-80%	F9	1700	129	1751	
RPV98 490x592x292	490	592	292	ePM1-80%	F9	2850	129	1751	

Custom sizes available on request