

RPV SC



Compact filters in V-form, filter coarse ISO ePM10-70%, ISO ePM1-60%, ISO ePM1-75%, ISO ePM1-85%

APPLICATIONS

- Filtration for air handling units equipped with a pre-filter
- Pre-filter for Cleanroom application

BENEFITS

- Large filter surface
- High filter efficiency
- Eurovent certified

SPECIFICATIONS

- Medium: Minipleated glass fiber paper
- Frame: Polystyrene plastic
- Seal: Polyurethane
- Spacers: Hot-melt cord
- Recommended final pressure drop: 250Pa
- Max. continuous temperature: 70°C
- Max. relative humidity: 100%



DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	THICKNESS (C) MM	ISO COARSE 16890	CLASS EN 779:2012	FLOW RATE m³/U	ΔP INITIAL	KWH/J 4/21-2018	ENERGY CLASS
RPV65 SC 592x592x292	592	592	292	ePM10-70%	M6	3400	69	945	D
RPV65 SC 288x592x292	288	592	292	ePM10-70%	M6	1700	69	945	
RPV65 SC 490x592x292	490	592	292	ePM10-70%	M6	2850	69	945	
RPV85 SC 592x592x292	592	592	292	ePM1-60%	F7	3400	76	945	A
RPV85 SC 288x592x292	288	592	292	ePM1-60%	F7	1700	76	945	
RPV85 SC 490x592x292	490	592	292	ePM1-60%	F7	2850	76	945	
RPV95 SC 592x592x292	592	592	292	ePM1-75%	F8	3400	90	1437	C
RPV95 SC 288x592x292	288	592	292	ePM1-75%	F8	1700	90	1437	
RPV95 SC 490x592x292	490	592	292	ePM1-75%	F8	2850	90	1437	
RPV98 SC 592x592x292	592	592	292	ePM1-85%	F9	3400	118	1519	C
RPV98 SC 288x592x292	288	592	292	ePM1-85%	F9	1700	118	1519	
RPV98 SC 490x592x292	490	592	292	ePM1-85%	F9	2850	118	1519	

Custom sizes available on request