## IFBS SIDE FILTERHOUSING

Feature: Ergonomic and easy to open

## **APPLICATIONS**

Heavy industrial applications. Coarse filtration (>500 micron), medium filtration (<10 micron), pre-filtration, safety filtration, batch filtration, round pump filtration, solvents, lacquers, fats and oils, acids and bases, water and waste water, petrochemicals, chemical industry, metal cleaning, food and beverages, paints and lacquers, water treatment and galvanic industry.

## **FEATURE**

 No leakage of fluid when opened. Ergonomic and easy to open. Good sealing of the filter bag (360 °C). Perfect support and easy to clean.



LENGTH SIZE OF POCKET FILTER	MATERIAL STAINLESS STEEL 304 316		CONNECTION BSP 2" DN50		Debit M3/H	NUMBER OF BAGS	MAX PRESSURE 10 BAR	SURFACE TREATMENT PS EP MP EMP				PACKING B E V T S				CONFIRMATI TC CL		
01	√	√	√	√	20	1	√	√	√	√	√	√	√	√	√	√	√	√
02	√	√	√	√	40	1	√	√	√	√	√	√	√	√	√	√	√	√
03	√	√	√	√	6	1	√	√	√	√	√	√	√	√	√	√	√	√
04	√	√	√	√	12	1	√	√	√	√	√	√	√	√	√	√	√	√

<sup>\*</sup> Surface treatment



<sup>:</sup> PS = Glass blasting, EP = Electropolishing, MP = Mechanical polishing and EMP electro and mechanical polishing.

<sup>\*</sup> Gasket

<sup>:</sup> B = Buna-N (NBR, Nitrile), E = EPDM, V = Viton, T = Teflon and S = Silicone.

<sup>\*</sup> Closure : TC = Bolt lock, CL = Lock quick lock.

<sup>\*</sup> Special connections and mountings on request.