

KG18 MODULES

Plastic filter modules filled with molecular filter medium

APPLICATIONS

- Capturing odors and gases

BENEFITS

- Robust and high-quality construction
- High airflow capacity with low resistance thanks to V-shape
- Fully recyclable housing
- Available with various types of filling, tailored to the nature of the contaminants to be captured

SPECIFICATIONS

- Supplied in pairs for a width of 610mm (24")
- Volume: 15 liters per pair
- Weight: Depends on the applied medium
- The specific mass can vary by medium type
- Material: 100% recyclable plastic or steel
- Carbon bed thickness: 25mm
- Max. continuous temperature: 55°C
- Max. relative humidity: 20-99%, depending on the applied filter medium



DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	DEPTH (C) MM	AIRFLOW M3/H	CONTACT TIME SEC	INITIAL ΔP
KG module 18	296	145	439	42	0,577	4
KG module 18	296	145	439	83	0,289	6
KG module 18	296	145	439	111	0,217	8
KG module 18	296	145	439	125	0,192	9
KG module 18	296	145	439	167	0,144	13
KG module 18	296	145	439	209	0,115	18
KG module 18	296	145	439	250	0,096	24
KG module 18	296	145	439	292	0,082	30
KG module 18	296	145	439	334	0,075	37
KG module 18	296	145	439	376	0,064	45
KG module 18	296	145	439	417	0,058	53
KG module 18	296	145	439	444	0,054	58