

DEDUSTING BAGS

Custom made in various filtermedia

APPLICATIONS

- Pharmaceutical industry, food industry, chemical industry, wood processing, rubber and plastic production, silo ventilation, metalworking, foundries, waste incineration, ceramic industry, coal extraction, power plants, mining and various other processes.

CERTIFICATION

- Available, if applicable, with food grade or ATEX certificate.



TYPE MEDIA	MATERIAL	CODE ACCORDING TO DIN60001	WEIGHT GR/M2	TREATMENT OR COATING	MAX. TEMP. CONTINUOUS	PEAK	MICRON SIZE					
							1	2	3	4	5	
PAN500	ACRYL	PAN	500	Smooth finish on fabric side	130-135 °C	130-135 °C	✓					
CO300	COTTON	CO	300	Smooth finish on fabric side	90-100 °C	110 °C	✓					
CO200	COTTON	CO	200	Smooth finish on fabric side	90-100 °C	110 °C	✓					
CO250	COTTON	CO	250	Smooth finish on fabric side	90-100 °C	110 °C	✓					
PES270	POLYESTER	PES	270	Smooth finish on fabric side	130-135 °C	140 °C	✓	✓	✓	✓	✓	✓
PES400	POLYESTER	PES	400	Smooth finish on fabric side	130-135 °C	140 °C	✓	✓	✓	✓	✓	✓
PES500	POLYESTER	PES	500	Smooth finish on fabric side	130-135 °C	140 °C	✓	✓	✓	✓	✓	✓
PES550	POLYESTER	PES	550	Smooth finish on fabric side	130-135 °C	140 °C	✓	✓	✓	✓	✓	✓
PAI500	ARAMIDA	PAI	500	Smooth finish on fabric side	200-220 °C	260 °C	✓	✓	✓	✓	✓	✓
PPS500	SULFAR	PPS	500	Smooth finish on fabric side	180 °C	200 °C	✓	✓	✓	✓	✓	✓
PES300	POLYESTER	PES	300	Smooth finish on fabric side	130-135 °C	140 °C	✓	✓	✓			✓
PP500	POLYPROPYLENE	PP	500	Smooth finish on fabric side	80-90 °C	90-100 °C	✓	✓	✓			✓
PES400AL	POLYESTER	PES	400	Smooth finish on fabric side	130-135 °C	140 °C	✓	✓	✓	✓	✓	✓
PES500AL	POLYESTER	PES	500	Smooth finish on fabric side	130-135 °C	140 °C	✓	✓	✓	✓	✓	✓
PES550AL	POLYESTER	PES	550	Smooth finish on fabric side	130-135 °C	140 °C	✓	✓	✓	✓	✓	✓
PES500OWR	POLYESTER	PES	500	Smooth finish on fabric side	130-135 °C	140 °C	✓	✓	✓	✓	✓	✓
PES400EX	POLYESTER	PES	400	Smooth finish on fabric side	130-135 °C	140 °C	✓	✓	✓	✓	✓	✓
PES500EX	POLYESTER	PES	500	Smooth finish on fabric side	130-135 °C	140 °C	✓	✓	✓	✓	✓	✓
PES550EX	POLYESTER	PES	550	Smooth finish on fabric side	130-135 °C	140 °C	✓	✓	✓	✓	✓	✓

CODE TREATMENT OR COATING

- 1 PTFE (TEFLON) COATING
- 2 OIL AND WATER
- 3 REPELLENT FLAME
- 4 RETARDANT ANTI
- 5 HYDROLIC ANTI ADHESIVE



Different filter media and treatments on request.