

G95

Bag filters with a fiberglass medium,
filter class ISO ePM1-85%



APPLICATIONS

- Fine filtration for air handling units and pre-filtration for (H)EPA filters

BENEFITS

- The aerodynamic design reduces turbulence in the airflow
- Tapered stitched bags reduce pressure drop
- Low energy consumption
- High dust-holding capacity
- Long lifespan
- Eurovent certified

SPECIFICATIONS

- Medium: Fiberglass
- Frame: Steel, also available in wood and plastic
- Recommended final resistance: 250 Pa
- Max. continuous temperature: 70°C
- Max. relative humidity: 100%



DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	LENGTH (C) MM	NUMBER OF POCKETS	ISO COARSE 16890	CLASS EN 779:2012	FLOW RATE m³/U	ΔP INITIAL	KWH/J 4/21-2018	ENERGY CLASS
G95 592x592x535, 10p	592	592	535	10	ePM1-85%	F8/F9	3400	165	2107	D
G95 288x592x535, 5p	288	592	535	5	ePM1-85%	F8/F9	1700	165	2107	
G95 490x592x535, 8p	490	592	535	8	ePM1-85%	F8/F9	2800	165	2107	
G95 592x592x635, 8p	592	592	635	8	ePM1-85%	F8/F9	3400	160	2054	D
G95 288x592x635, 4p	288	592	635	4	ePM1-85%	F8/F9	1700	160	2054	
G95 490x592x635, 6p	490	592	635	6	ePM1-85%	F8/F9	2800	160	2054	
G95 592x592x635, 10p	592	592	635	10	ePM1-85%	F8/F9	3400	145	1863	D
G95 288x592x635, 5p	288	592	635	5	ePM1-85%	F8/F9	1700	145	1863	
G95 490x592x635, 8p	490	592	635	8	ePM1-85%	F8/F9	2800	145	1863	

Custom sizes available on request.