

G95

Bag filters with a fiberglass medium,
filter class ISO ePM1-85%

APPLICATIONS

- Fine filtration for air handling units and pre-filtration for (H)EPA filters

BENEFITS

- The aerodynamic design reduces turbulence in the airflow
- Tapered stitched bags reduce pressure drop
- Low energy consumption
- High dust-holding capacity
- Long lifespan
- Eurovent certified via the manufacturer Deltrian

SPECIFICATIONS

- Medium: Fiberglass
- Frame: Steel, also available in wood and plastic
- Recommended final resistance: 250 Pa
- Max. continuous temperature: 70°C
- Max. relative humidity: 100%



ITEM NO.	DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	LENGTH (C) MM	NUMBER OF POCKETS	CLASS ISO 16890	CLASS EN779:2012 M3/U	AIRFLOW	ΔP INITIAL	KWH/J 4/21-2018
02210	G95 592x592x600, 8p	592	592	600	8	ePM1-85%	F9	3400	160	2045
02211	G95 288x592x600, 4p	288	592	600	4	ePM1-85%	F9	1700	160	2045
02212	G95 490x592x600, 6p	490	592	600	6	ePM1-85%	F9	2800	160	2045
02218	G95 288x288x600, 4p	288	288	600	4	ePM1-85%	F9	850	160	2045
02220	G95 592x288x600, 8p	592	288	600	8	ePM1-85%	F9	1700	160	2045
02219	G95 592x490x600, 8p	592	490	600	8	ePM1-85%	F9	2800	160	2045
02231	G95 592x892x600, 8p	592	892	600	8	ePM1-85%	F9	5100	160	2045
02232	G95 288x892x600, 4p	288	892	600	4	ePM1-85%	F9	2550	160	2045
02233	G95 490x892x600, 6p	490	892	600	6	ePM1-85%	F9	4200	160	2045

Custom sizes available on request.