

SGK85 EN GK85

Hybrid bag filter with a combination of fiberglass and synthetic filter medium, filter class ISO ePM1-60% and ISO ePM1-70%

APPLICATIONS

- Fine filtration for air handling units
- Prefiltration for (H)EPA filters

BENEFITS

- Extremely high dust-holding capacity
- Reduced risk of filter fiber migration
- Eurovent certified by the manufacturer Deltrian

SPECIFICATIONS

- Medium: Fiberglass fine filter with synthetic inner layer
- Frame: Steel, also available in wood and plastic
- Recommended final resistance: 250Pa
- Max. continuous temperature: 70°C
- Max. relative humidity: 100%



ARTICLE NO.	DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	LENGTH (C) MM	NUMBER OF POCKETS	ISO 16890 CLASS	EN779:2012 CLASS M3/U	AIRFLOW	INITIAL ΔP	KWH/J 4/21-2018
32110	SGK85 592x592x600, 8p	592	592	600	8	ePM1-60%	F7	3400	108	1333
31114	SGK85 288x592x600, 4p	288	592	600	4	ePM1-60%	F7	1700	108	1333
32112	SGK85 490x592x600, 6p	490	592	600	6	ePM1-60%	F7	2800	108	1333
32118	SGK85 288x288x600, 4p	288	288	600	4	ePM1-60%	F7	850	108	1333
32120	SGK85 592x288x600, 8p	592	288	600	8	ePM1-60%	F7	1700	108	1333
32119	SGK85 592x490x600, 8p	592	490	600	8	ePM1-60%	F7	2800	108	1333
32149	SGK85 592x892x600, 8p	592	892	600	8	ePM1-60%	F7	5100	108	1333
32150	SGK85 288x892x600, 4p	288	892	600	4	ePM1-60%	F7	2550	108	1333
14110	GK85 592x592x600, 8p	592	592	600	8	ePM1-70%	F8	3400	120	1462
14111	GK85 288x592x600, 4p	288	592	600	4	ePM1-70%	F8	1700	120	1462
14112	GK85 490x592x600, 6p	490	592	600	6	ePM1-70%	F8	2800	120	1462
14118	GK85 288x288x600, 4p	288	288	600	4	ePM1-70%	F8	850	120	1462
14120	GK85 592x288x600, 8p	592	288	600	8	ePM1-70%	F8	1700	120	1462
14119	GK85 592x490x600, 8p	592	490	600	8	ePM1-70%	F8	2800	120	1462
14149	GK85 592x892x600, 8p	592	892	600	8	ePM1-70%	F8	5100	120	1462
14150	GK85 288x892x600, 4p	288	892	600	4	ePM1-70%	F8	2550	120	1462

Custom dimensions available upon request.