

SGK85 AND GK85

Hybrid bag filter,
filter class ISO ePM1-60% and ISO ePM1-70%



APPLICATIONS

- Fine filtration for air handling units and pre-filtration for (H)EPA filters

BENEFITS

- Extremely high dust-holding capacity
- Reduced risk of filter fiber migration
- Eurovent certified

SPECIFICATIONS

- Medium: Fiberglass fine filter with synthetic inner layer
- Frame: Steel, also available in wood and plastic
- Recommended final resistance: 250Pa
- Max. continuous temperature: 70°C
- Max. relative humidity: 100%



DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	LENGTH (C) MM	NUMBER OF POCKETS	ISO COARSE 16890	CLASS EN 779:2012	FLOW RATE m³/U	ΔP INITIAL	KWH/J 4/21-2018	ENERGY CLASS
SGK85 592x592x635, 8p	592	592	635	8	ePM1-60%	F7	3400	108	1333	C
SGK85 288x592x635, 4p	288	592	635	4	ePM1-60%	F7	1700	108	1333	
SGK85 490x592x635, 6p	490	592	635	6	ePM1-60%	F7	2800	108	1333	
SGK85 288x288x635, 4p	288	288	635	4	ePM1-60%	F7	850	108	1333	
GK85 592x592x635, 8p	592	592	635	8	ePM1-70%	F8	3400	120	1462	C
GK85 288x592x635, 4p	288	592	635	4	ePM1-70%	F8	1700	120	1462	
GK85 490x592x635, 6p	490	592	635	6	ePM1-70%	F8	2800	120	1462	
GK85 288x288x635, 4p	288	288	635	4	ePM1-70%	F8	850	120	1462	

Custom sizes available on request.