

IFSSPS FILTERCARTRIDGE

STANDARD RANGE,

Features: Cleanable, heavy duty

APPLICATIONS

- Filtration of aggressive liquids where a robust filter is necessary.

FEATURE

- FDA approved.
- 316L stainless steel, pleated medium
- Pleated medium and connections TIG welded.
- Cleanable by reverse flow, chemical, ultrasonic and high temperature combustion.
- Maximum operating temperature 260 °C
- Maximum operating pressure difference 4.2 bar.
- Maximum pressure difference at reverse flow 1 bar.



LENGTH TYPE	SIZE	MICRON SIZE					
		40	75	100	250	500	850
9 3/4	9 3/4"	√	√	√	√	√	√
10	10"	√	√	√	√	√	√
20	20"	√	√	√	√	√	√
30	30"	√	√	√	√	√	√
40	40"	√	√	√	√	√	√

Length in inches : 9 3/4, 10, 20, 30 in 40

Length in mm : 248, 254, 508, 762, 1016

Micron size : 40, 75, 100, 250, 500, 850

Gasket : Cotton, Teflon, EPDM of Vitton

Outer diameter : 67 mm

Inner diameter : 27 mm

Max. operating temp. : 260 oC

Max. operational pressure difference : 4.2 bar

Max. pressure difference during reverse flow : 1 bar