

IFSSPP FILTERCARTRIDGE

PREMIER RANGE, Feature: Cleanable, extra heavy duty

APPLICATIONS

- Filtration of aggressive liquids where a robust filter is necessary.

FEATURE

- FDA approved.
- 316L stainless steel, pleated medium and support basket.
- Pleated medium, support basket and connections TIG welded
- Cleanable by reverse-flow, chemical, ultrasonic and high-temperature combustion.
- Maximum operating temperature 360 °C at 5 bar
- Maximum operational pressure difference 5 bar.
- Maximum pressure difference at reverse flow 3 bar.



LENGTH TYPE	SIZE	MICRON SIZE								
		5	10	20	40	75	100	250	500	
10	10"	√	√	√	√	√	√	√	√	
20	20"	√	√	√	√	√	√	√	√	
30	30"	√	√	√	√	√	√	√	√	
40	40"	√	√	√	√	√	√	√	√	

Length in inches	: 10, 20, 30 and 40
Length in mm	: Depending on the type of end cap
Micron size	: 5, 10, 20, 40, 75, 100, 250, 500
End cap/gasket	: Open, closed or fin / Teflon, EPDM or Viton
Outer diameter	: 65 mm
Inner diameter	: 27 mm
Max. operating temp.	: 360 °C at 5 bar
Max. operational pressure difference	: 5 bar
Max. pressure difference during reverse flow	: 3 bar