

FZK55

Panel filters with pleated filter cloth and plastic frame, filter class ISO ePM10-50%

APPLICATIONS

- Medium class filtration in air handling units or for inlet grilles
- Pre-filtration for fine filters

ADVANTAGES

- Large filter surface for a long service life
- High dust-holding capacity
- Easy to install and to replace
- Fire-resistant medium class M1 available on request
- Moisture resistant
- High strength

CHARACTERISTICS

- Media: Synthetic Frame: Plastic
- Recommended final pressure drop: 250Pa
- Max. continuous temperature: 70 degrees celsius
- Max. relative humidity: 100%



ITEM NO.	DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	THICKNESS (C) MM	CLASS ISO 16890	CLASS E N 779:2012	FLOW RATE M3/U	ΔP INITIAL
29352	FZK55 24x24x2	592	592	45	ePM10-50%	M5	3785	110
29910	FZK55 12x24x2	288	592	45	ePM10-50%	M5	1840	110
26855	FZK55 20x24x2	490	592	45	ePM10-50%	M5	3130	110
	FZK55 12x12x2	288	288	45	ePM10-50%	M5	895	110
	FZK55 16x20x2	395	490	45	ePM10-50%	M5	2090	110
	FZK55 16x25x2	395	624	45	ePM10-50%	M5	2660	110
	FZK55 20x20x2	490	490	45	ePM10-50%	M5	2595	110
	FZK55 20x25x2	490	624	45	ePM10-50%	M5	3300	110
29152	FZK55 16x24x2	395	592	45	ePM10-50%	M5	2525	110
28647	FZK55 24x24x4	592	592	96	ePM10-50%	M5	3785	60
28794	FZK55 12x24x4	288	592	96	ePM10-50%	M5	1840	60
28510	FZK55 20x24x4	490	592	96	ePM10-50%	M5	3130	60
28931	FZK55 12x12x4	288	288	96	ePM10-50%	M5	895	60
103966	FZK55 16x20x4	395	490	96	ePM10-50%	M5	2090	60
30301	FZK55 16x25x4	395	624	96	ePM10-50%	M5	2660	60
	FZK55 20x20x4	490	490	96	ePM10-50%	M5	2595	60
	FZK55 20x25x4	490	624	96	ePM10-50%	M5	3300	60
	FZK55 16x24x4	395	592	96	ePM10-50%	M5	2525	60