

# FZG35

Panel filters with pleated filter media and galvanized steel frame, filter class ISO Coarse-65%

## APPLICATIONS

- Medium class filtration in air handling units or intake grilles
- Pre-filtration for fine filters

## BENEFITS

- Large filter surface for long service life
- High dust holding capacity
- Easy to install and replace panel filter
- Filter medium supported on both sides by mesh
- Fireproof medium class M1 available on request
- Moisture resistant
- Mechanically very strong

## SPECIFICATIONS

- Medium: Synthetic
- Frame: Galvanized steel or plastic
- Recommended final resistance: 250Pa
- Max. continuous temperature: 110°C
- Max. relative humidity: 100%



ARTICLE NO.	DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	DEPTH (C) MM	CLASS ISO 16890	CLASS EN779:2012	FLOW RATE M3/U	ΔP INITIAL
23730	<b>FZG35 24x24x2</b>	592	592	48	Coarse-65%	G4	3785	70
23731	<b>FZG35 12x24x2</b>	288	592	48	Coarse-65%	G4	1840	70
23854	<b>FZG35 20x24x2</b>	490	592	48	Coarse-65%	G4	3130	70
24975	<b>FZG35 12x12x2</b>	288	288	48	Coarse-65%	G4	895	70
24464	<b>FZG35 16x20x2</b>	395	490	48	Coarse-65%	G4	2090	70
24465	<b>FZG35 16x25x2</b>	395	624	48	Coarse-65%	G4	2660	70
24466	<b>FZG35 20x20x2</b>	490	490	48	Coarse-65%	G4	2595	70
24467	<b>FZG35 20x25x2</b>	490	624	48	Coarse-65%	G4	3300	70
27773	<b>FZG35 24x24x4</b>	592	592	96	Coarse-65%	G4	3785	60
23745	<b>FZG35 12x24x4</b>	288	592	96	Coarse-65%	G4	1840	60
26120	<b>FZG35 20x24x4</b>	490	592	96	Coarse-65%	G4	3130	60
25975	<b>FZG35 12x12x4</b>	288	288	96	Coarse-65%	G4	895	60
28525	<b>FZG35 16x20x4</b>	395	490	96	Coarse-65%	G4	2090	60
28679	<b>FZG35 16x25x4</b>	395	624	96	Coarse-65%	G4	2660	60
27993	<b>FZG35 20x20x4</b>	490	490	96	Coarse-65%	G4	2595	60
27751	<b>FZG35 20x25x4</b>	490	624	96	Coarse-65%	G4	3300	60
25796	<b>FZG35 16x24x4</b>	395	592	96	Coarse-65%	G4	2525	60

Also available with plastic frame (FZPL). Custom sizes available upon request.