

FZG55

Flat filters with pleated filter cloth and galvanized steel frame, filter class ISO ePM10-50%

APPLICATION

- Medium class filtration in air handling units or for intake grilles
- Pre-filtration for fine filters

BENEFITS

- Large filter surface for extended service life
- High dust holding capacity
- Easy-to-install and replace panel filter
- Filter medium supported by mesh on both sides
- Fire-resistant medium, class M1 available upon request
- Moisture-resistant
- Mechanically robust

PROPERTIES

- Medium: Synthetic
- Frame: Galvanized steel or plastic
- Recommended final resistance: 250Pa
- Max. continuous temperature: 110 degrees Celsius
- Max. relative humidity: 100%



ARTICLENR.	DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	LENGTH (C) MM	NR. OF POCKETS	CLASS ISO 16890	CLASS EN779:2012	FLOW M ³ /U	ΔP RESISTANCE	KWH/J 4/21-2018
26560	FZG55 24x24x2	592	592	48		ePM10-50%	M5	3785		110
25189	FZG55 12x24x2	288	592	48		ePM10-50%	M5	1840		110
25764	FZG55 20x24x2	490	592	48		ePM10-50%	M5	3130		110
25188	FZG55 12x12x2	288	288	48		ePM10-50%	M5	895		110
25765	FZG55 16x20x2	395	490	48		ePM10-50%	M5	2090		110
29199	FZG55 16x25x2	395	624	48		ePM10-50%	M5	2660		110
29200	FZG55 20x20x2	490	490	48		ePM10-50%	M5	2595		110
29203	FZG55 20x25x2	490	624	48		ePM10-50%	M5	3300		110
28490	FZG55 16x24x2	395	592	48		ePM10-50%	M5	2525		110
28949	FZG55 24x24x4	592	592	96		ePM10-50%	M5	3785		100
29204	FZG55 12x24x4	288	592	96		ePM10-50%	M5	1840		60
25958	FZG55 20x24x4	490	592	96		ePM10-50%	M5	3130		60
29205	FZG55 12x12x4	288	288	96		ePM10-50%	M5	895		60
29206	FZG55 16x20x4	395	490	96		ePM10-50%	M5	2090		60
28758	FZG55 16x25x4	395	624	96		ePM10-50%	M5	2660		60
29207	FZG55 20x20x4	490	490	96		ePM10-50%	M5	2595		60
29208	FZG55 20x25x4	490	624	96		ePM10-50%	M5	3300		60
29209	FZG55 16x24x4	395	592	96		ePM10-50%	M5	2525		60

Custom sizes available upon request