

FZMP

Flat filters with minipleated filter medium,
filter class ISO ePM10-55%, ISO ePM10-70%

APPLICATIONS

- Medium filtration for air handling units with a pre-filter

BENEFITS

- Limited installation sizes
- Large filter surface
- Eurovent certified by manufacturer Deltrian

SPECIFICATIONS

- Medium: Minipleated fiberglass paper
- Frame: Plastic, also available in galvanized steel and MDF
- Spacers: Hot-melt cord
- Max. continuous temperature: 60°C
- Max. relative humidity: 100%



ARTICLE NO.	DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	DEPTH (C) MM	CLASS ISO 16890	CLASS EN779:2012	FLOW RATE M3/U	ΔP INITIAL
50014	FZMP50 24x24x2	592	592	48	ePM10-55%	M5	2500	50
50015	FZMP50 12x24x2	288	592	48	ePM10-55%	M5	1250	50
24495	FZMP50 20x24x2	490	592	48	ePM10-55%	M5	2075	50
24644	FZMP50 12x12x2	288	288	48	ePM10-55%	M5	625	50
50127	FZMP50 24x24x4	592	592	96	ePM10-55%	M5	3350	85
50128	FZMP50 12x24x4	288	592	96	ePM10-55%	M5	1675	85
50244	FZMP50 20x24x4	490	592	96	ePM10-55%	M5	2775	85
50129	FZMP50 12x12x4	288	288	96	ePM10-55%	M5	835	85
55000	FZMP65 24x24x2	592	592	48	ePM10-70%	M6	2000	42
105411	FZMP65 12x24x2	288	592	48	ePM10-70%	M6	1000	42
50240	FZMP65 20x24x2	490	592	48	ePM10-70%	M6	1667	42
50432	FZMP65 12x12x2	288	288	48	ePM10-70%	M6	500	42
50241	FZMP65 24x24x4	592	592	96	ePM10-70%	M6	2880	81
50232	FZMP65 12x24x4	288	592	96	ePM10-70%	M6	1440	81
50240	FZMP65 20x24x4	490	592	96	ePM10-70%	M6	2400	81
50433	FZMP65 12x12x4	288	288	96	ePM10-70%	M6	720	81

Custom sizes on request.