

FZMP65-FZMP85

Panel filters with minipleated filter medium,
filter class ISO ePM10-70%, ISO ePM1-60%



APPLICATIONS

- Medium filtration for air handling units with a pre-filter

BENEFITS

- Compact installation dimensions
- Large filter surface area
- Eurovent certified

SPECIFICATIONS

- Medium: Minipleated fiberglass paper
- Frame: Plastic, also available in galvanized steel and MDF
- Spacers: Hot-melt cord
- Max. continuous temperature: 70°C
- Max. relative humidity: 100%



ART. NO.	DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	THICKNESS (C) MM	CLASS ISO 16890	CLASS EN779:2012	FLOW RATE m³/U	ΔP INITIAL	KWH/YEAR 4/21-2018
55000	FZMP65 24x24x2	592	592	45	ePM10-70%	M6	2000	42	>1300
105411	FZMP65 12x24x2	288	592	45	ePM10-70%	M6	1000	42	>1300
50240	FZMP65 20x24x2	490	592	45	ePM10-70%	M6	1700	42	>1300
50432	FZMP65 12x12x2	288	288	45	ePM10-70%	M6	500	42	>1300
50241	FZMP65 24x24x4	592	592	96	ePM10-70%	M6	2880	81	>1300
50232	FZMP65 12x24x4	288	592	96	ePM10-70%	M6	1440	81	>1300
50240	FZMP65 20x24x4	490	592	96	ePM10-70%	M6	2390	81	>1300
50433	FZMP65 12x12x4	288	288	96	ePM10-70%	M6	720	81	>1300
23520	FZMP85 24x24x2	592	592	45	ePM1-60%	F7	2000	69	>2050
50017	FZMP85 12x24x2	288	592	45	ePM1-60%	F7	1000	69	>2050
50221	FZMP85 20x24x2	490	592	45	ePM1-60%	F7	1700	69	>2050
50434	FZMP85 12x12x2	288	288	45	ePM1-60%	F7	500	69	>2050
50226	FZMP85 24x24x4	592	592	96	ePM1-60%	F7	2880	90	>2050
50227	FZMP85 12x24x4	288	592	96	ePM1-60%	F7	1440	90	>2050
50242	FZMP85 20x24x4	490	592	96	ePM1-60%	F7	2390	90	>2050
50288	FZMP85 12x12x4	288	288	96	ePM1-60%	F7	720	90	>2050

Different sizes available on request