

# FZMP95-FZMP98

Panel filters with minipleated filter medium,  
filter class ISO ePM1-70%, ISO ePM1-80%



## APPLICATIONS

- Fine filtration for air handling units with a pre-filter

## BENEFITS

- Compact and cost-effective
- Large filter surface area
- Eurovent certified

## SPECIFICATIONS

- Medium: Minipleated fiberglass paper
- Frame: Plastic, also available in galvanized steel and MDF
- Spacers: Hot-melt cord
- Max. continuous temperature: 60°C
- Max. relative humidity: 100%



| ART. NO. | DESCRIPTION           | WIDTH<br>(A) MM | HEIGHT<br>(B) MM | THICKNESS<br>(C) MM | CLASS<br>ISO 16890 | CLASS<br>EN779:2012 | FLOW RATE<br>m³/U | ΔP<br>INITIAL | KWH/YEAR<br>4/21-2018 |
|----------|-----------------------|-----------------|------------------|---------------------|--------------------|---------------------|-------------------|---------------|-----------------------|
| 50342    | <b>FZMP95 24x24x2</b> | 592             | 592              | 45                  | ePM1-70%           | F8                  | 2000              | 96            | >2150                 |
| 50435    | <b>FZMP95 12x24x2</b> | 288             | 592              | 45                  | ePM1-70%           | F8                  | 1000              | 96            | >2150                 |
| 50436    | <b>FZMP95 20x24x2</b> | 490             | 592              | 45                  | ePM1-70%           | F8                  | 1700              | 96            | >2150                 |
| 50469    | <b>FZMP95 12x12x2</b> | 288             | 288              | 45                  | ePM1-70%           | F8                  | 500               | 96            | >2150                 |
| 50273    | <b>FZMP95 24x24x4</b> | 592             | 592              | 96                  | ePM1-70%           | F8                  | 2880              | 100           | >2150                 |
| 50216    | <b>FZMP95 12x24x4</b> | 288             | 592              | 96                  | ePM1-70%           | F8                  | 1440              | 100           | >2150                 |
| 50275    | <b>FZMP95 20x24x4</b> | 490             | 592              | 96                  | ePM1-70%           | F8                  | 2390              | 100           | >2150                 |
| 50271    | <b>FZMP95 12x12x4</b> | 288             | 288              | 96                  | ePM1-70%           | F8                  | 720               | 100           | >2150                 |
| 50437    | <b>FZMP98 24x24x2</b> | 592             | 592              | 45                  | ePM1-80%           | F9                  | 2000              | 145           | >2400                 |
| 50438    | <b>FZMP98 12x24x2</b> | 288             | 592              | 45                  | ePM1-80%           | F9                  | 1000              | 145           | >2400                 |
| 50439    | <b>FZMP98 20x24x2</b> | 490             | 592              | 45                  | ePM1-80%           | F9                  | 1700              | 145           | >2400                 |
| 50440    | <b>FZMP98 12x12x2</b> | 288             | 288              | 45                  | ePM1-80%           | F9                  | 500               | 145           | >2400                 |
| 24000    | <b>FZMP98 24x24x4</b> | 592             | 592              | 96                  | ePM1-80%           | F9                  | 2880              | 130           | >2400                 |
| 23999    | <b>FZMP98 12x24x4</b> | 288             | 592              | 96                  | ePM1-80%           | F9                  | 1440              | 130           | >2400                 |
| 25169    | <b>FZMP98 20x24x4</b> | 490             | 592              | 96                  | ePM1-80%           | F9                  | 2390              | 130           | >2400                 |
| 50441    | <b>FZMP98 12x12x4</b> | 288             | 288              | 96                  | ePM1-80%           | F9                  | 720               | 130           | >2400                 |

*Different sizes available on request*