

# K+85

Bag filter with synthetic filter medium,  
filter class ISO ePM1-60%

## APPLICATIONS

- Filtration for air handling units

## BENEFITS

- HIGH-TECH aerodynamic profile that limits turbulence at the air outlet
- Low pressure drop across the filter
- Conical pockets
- Suitable for use in food industry facilities
- Eurovent certified through the manufacturer Deltrian

## SPECIFICATIONS

- Medium: Synthetic
- Frame: Steel, also available in wood and plastic
- Recommended final resistance: 300 Pa
- Maximum continuous temperature: 70°C
- Maximum relative humidity: 100% RH



ARTICLE NO.	DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	LENGTH (C) MM	NUMBER OF POCKETS	CLASS ISO 16890	CLASS EN779:2012	FLOW RATE M3/U	ΔP INITIAL	KWH/J 4/21-2018
033121	<b>K+85 592x592x500, 8p</b>	592	592	500	8	ePM1-60%	F7	3400	120	>2050
033160	<b>K+85 288x592x500, 4p</b>	288	592	500	4	ePM1-60%	F7	1700	120	
033167	<b>K+85 592x288x500, 8p</b>	592	288	500	8	ePM1-60%	F7	1700	120	
033138	<b>K+85 288x288x500, 4p</b>	288	288	500	4	ePM1-60%	F7	850	120	
033110	<b>K+85 592x592x600, 8p</b>	592	592	600	8	ePM1-60%	F7	3400	110	1708
033111	<b>K+85 288x592x600, 4p</b>	288	592	600	4	ePM1-60%	F7	1700	110	
033120	<b>K+85 592x288x600, 8p</b>	592	288	600	8	ePM1-60%	F7	1700	110	
033118	<b>K+85 288x288x600, 4p</b>	288	288	600	4	ePM1-60%	F7	850	110	

Custom sizes on request.