

K+85

Bag filter with synthetic filter medium,
filter class ISO ePM1-60%



APPLICATIONS

- Filtration for air handling units

BENEFITS

- HIGH-TECH aerodynamic profile that limits turbulence at the air outlet
- Low pressure drop across the filter
- Conical pockets
- Suitable for use in food industry facilities
- Eurovent certified

SPECIFICATIONS

- Medium: Synthetic
- Frame: Steel, also available in wood, plastic or reusable LFC frame
- Recommended final resistance: 300 Pa
- Maximum continuous temperature: 70°C
- Maximum relative humidity: 100%



DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	LENGTH (C) MM	NUMBER OF POCKETS	ISO COARSE 16890	CLASS EN 779:2012	FLOW RATE m³/U	ΔP INITIAL	KWH/J 4/21-2018	ENERGY CLASS
K+85 592x592x535, 6p	592	592	535	6	ePM1-60%	F7	3400	157	>2050	E
K+85 288x592x535, 3p	288	592	535	3	ePM1-60%	F7	1700	157	>2050	
K+85 490x592x535, 5p	490	592	535	5	ePM1-60%	F7	2800	157	>2050	
K+85 592x592x535, 8p	592	592	535	8	ePM1-60%	F7	3400	125	>2050	E
K+85 288x592x535, 4p	288	592	535	4	ePM1-60%	F7	1700	125	>2050	
K+85 490x592x535, 6p	490	592	535	6	ePM1-60%	F7	2800	125	>2050	
K+85 592x592x635, 6p	592	592	635	6	ePM1-60%	F7	3400	138	1995	D
K+85 288x592x635, 3p	288	592	635	3	ePM1-60%	F7	1700	138	1995	
K+85 490x592x635, 5p	490	592	635	5	ePM1-60%	F7	2800	138	1995	
K+85 592x592x635, 8p	592	592	635	8	ePM1-60%	F7	3400	105	1708	D
K+85 288x592x635, 4p	288	592	635	4	ePM1-60%	F7	1700	105	1708	
K+85 490x592x635, 6p	490	592	635	6	ePM1-60%	F7	2800	105	1708	
K+85 592x592x635, 10p	592	592	635	10	ePM1-60%	F7	3400	96	1325	C
K+85 288x592x635, 5p	288	592	635	5	ePM1-60%	F7	1700	96	1325	
K+85 490x592x635, 8p	490	592	635	8	ePM1-60%	F7	2800	96	1325	

Custom sizes available on request.