

KS65

Pocket filters with synthetic filter medium,
filter class ISO ePM10-70%



APPLICATIONS

- Coarse (pre)filtration for air handling units and air inlet grilles
- Filtration of return and recirculation air

BENEFITS

- High dust holding capacity
- Low pressure drop across the filter
- Conical bags
- Applicable within food processing companies
- Eurovent certified

SPECIFICATIONS

- Medium: Synthetic with progressive construction
- Frame: Steel, also available in wood, plastic or a reusable LFC frame
- Recommended final resistance: 250Pa
- Max. continuous temperature: 70 °C
- Max. relative humidity: 100%



DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	LENGTH (C) MM	NUMBER OF POCKETS	ISO COARSE 16890	CLASS EN 779:2012	FLOW RATE m³/U	ΔP INITIAL	KWH/J 4/21-2018	ENERGY CLASS
KS65 592x592x380, 6p	592	592	380	6	ePM10-70%	M6	3400	72	>1300	E
KS65 288x592x380, 3p	288	592	380	3	ePM10-70%	M6	1700	72	>1300	
KS65 490x592x380, 5p	490	592	380	5	ePM10-70%	M6	2800	72	>1300	
KS65 592x592x380, 8p	592	592	380	8	ePM10-70%	M6	3400	58	>1300	E
KS65 288x592x380, 4p	288	592	380	4	ePM10-70%	M6	1700	58	>1300	
KS65 490x592x380, 6p	490	592	380	6	ePM10-70%	M6	2800	58	>1300	
KS65 592x592x500, 8p	592	592	500	8	ePM10-70%	M6	3400	63	>1300	E
KS65 288x592x500, 4p	288	592	500	4	ePM10-70%	M6	1700	63	>1300	
KS65 490x592x500, 6p	490	592	500	6	ePM10-70%	M6	2800	63	>1300	
KS65 592x592x600, 6p	592	592	600	6	ePM10-70%	M6	3400	54	>1300	E
KS65 288x592x600, 3p	288	592	600	5	ePM10-70%	M6	1700	54	>1300	
KS65 490x592x600, 5p	490	592	600	3	ePM10-70%	M6	2800	54	>1300	
KS65 592x592x600, 8p	592	592	600	8	ePM10-70%	M6	3400	50	>1300	E
KS65 288x592x600, 4p	288	592	600	4	ePM10-70%	M6	1700	50	>1300	
KS65 490x592x600, 6p	490	592	600	6	ePM10-70%	M6	2800	50	>1300	

Different sizes on request