

NW65

Bag filter with Nanowave synthetic filter medium, filter class ISO ePM10-55%

APPLICATIONS

- Low pressure drop
- Excellent dust retention capacity
- Self-supporting pockets
- Conical pockets designed to maximize performance
- Easy installation
- Tested for food contact according to CE 1935/2004

SPECIFICATIONS

- Filtration class according to ISO16890: 2016
- Media: Nanowave
- Recommended final resistance: 250Pa
- Maximum continuous service temperature: 80 °C
- Relative humidity: 100% RH



ARTICLE NO.	DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	LENGTH (C) MM	NUMBER OF POCKETS	CLASS ISO 16890	CLASS EN779:20212	FLOW RATE M3/U	ΔP INITIAL	KWH/J 4/21-2018
018073	NW65 592x592x500, 10p	592	592	500	10	ePM10-55%	M6	3400	51	631
018040	NW65 592x592x500, 8p	592	592	500	8	ePM10-55%	M6	3400	50	650
018089	NW65 592x592x600, 10p	592	592	600	10	ePM10-55%	M6	3400	47	582
018012	NW65 592x592x600,8p	592	592	600	8	ePM10-55%	M6	3400	47	590