

NW65

Bag filter with Nanowave synthetic filter medium,
filter class ISO ePM10-55%



APPLICATIONS

- Fine filtration for air handling units and pre-filtration for (H)EPA filters

BENEFITS

- Very low initial pressure drop
- High dust holding capacity, long service life
- Low energy consumption
- Self-supporting media
- Eurovent certified

SPECIFICATIONS

- Media: Nanowave synthetic
- Frame: Steel, also available in wood, plastic or reusable LFC frame
- Recommended final pressure drop: 250 Pa
- Max. continuous temperature: 80 °C
- Max. relative humidity: 100%



DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	LENGTH (C) MM	NUMBER OF POCKETS	ISO COARSE 16890	CLASS EN 779:2012	FLOW RATE m³/U	ΔP INITIAL	KWH/J 4/21-2018	ENERGY CLASS
NW65 592x592x535, 8p	592	592	535	8	ePM10-55%	M6	3400	50	650	B
NW65 288x592x535, 4p	288	592	535	4	ePM10-55%	M6	1700	50	650	
NW65 490x592x535, 6p	490	592	535	6	ePM10-55%	M6	2800	50	650	
NW65 592x592x635, 10p	592	592	635	10	ePM10-55%	M6	3400	51	631	B
NW65 288x592x635, 5p	288	592	635	5	ePM10-55%	M6	1700	51	631	
NW65 490x592x635, 8p	490	592	635	8	ePM10-55%	M6	2800	51	631	
NW65 592x592x635, 8p	592	592	635	8	ePM10-55%	M6	3400	47	590	B
NW65 288x592x635, 4p	288	592	635	4	ePM10-55%	M6	1700	47	590	
NW65 490x592x635, 6p	490	592	635	6	ePM10-55%	M6	2800	47	590	
NW65 592x592x635, 10p	592	592	635	10	ePM10-55%	M6	3400	47	582	B
NW65 288x592x635, 5p	288	592	635	5	ePM10-55%	M6	1700	47	582	
NW65 490x592x635, 8p	490	592	635	8	ePM10-55%	M6	2800	47	582	

Custom sizes available on request.