

# TNWES

Top New Wave Energy Savings bag filter with short pockets

## APPLICATIONS


- Fine filtration in air handling systems

## BENEFITS

- Very low pressure drop
- Excellent dust-holding capacity
- Self-supporting pockets
- Conical pockets designed for optimal performance
- Easy to install thanks to short pockets
- Tested for food contact according to CE 1935/2004

## SPECIFICATIONS

- Filter class according to ISO 16890 ePM1-70%
- Medium: TNWES (Top New Wave Energy Saving) synthetic
- Final pressure drop: 300 Pa (recommended 250 Pa)
- Maximum continuous operating temperature: 80°C
- Available with plastic or galvanized frame.



DESCRIPTION	LENGTH (A) MM	HEIGHT (B) MM	WIDTH (C) MM	CLASS ISO 16890	NUMBER OF POCKETS	FLOW RATE M3/U	ΔP INITIAL	KWH/J 4/21-2018	ENERGY LABEL
<b>TNWES 592x592x350</b>	592	592	350	ePM1-70%	10	3400	80	1217	B
<b>TNWES 288x592x350</b>	288	592	350	ePM1-70%	5	1700	80	1217	B
<b>TNWES 490x592x350</b>	490	592	350	ePM1-70%	8	2850	80	1217	B
<b>TNWES 288x288x350</b>	288	288	350	ePM1-70%	5	850	80	1217	B
<b>TNWES 592x288x350</b>	592	288	350	ePM1-70%	10	1700	80	1217	B
<b>TNWES 592x490x350</b>	592	490	350	ePM1-70%	10	2850	80	1217	B
<b>TNWES 592x592x450</b>	592	592	450	ePM1-70%	10	3400	69	946	A+
<b>TNWES 288x592x450</b>	288	592	450	ePM1-70%	5	1700	69	946	A+
<b>TNWES 490x592x450</b>	490	592	450	ePM1-70%	8	2850	69	946	A+
<b>TNWES 288x288x450</b>	288	288	450	ePM1-70%	5	850	69	946	A+
<b>TNWES 592x288x450</b>	592	288	450	ePM1-70%	10	1700	69	946	A+
<b>TNWES 592x490x450</b>	592	490	450	ePM1-70%	10	2850	69	946	A+
<b>TNWES 592x592x600</b>	592	592	600	ePM1-70%	10	3400	62	724	A+
<b>TNWES 288x592x600</b>	288	592	600	ePM1-70%	5	1700	62	724	A+
<b>TNWES 490x592x600</b>	490	592	600	ePM1-70%	8	2850	62	724	A+
<b>TNWES 288x288x600</b>	288	288	600	ePM1-70%	5	850	62	724	A+
<b>TNWES 592x288x600</b>	592	288	600	ePM1-70%	10	1700	62	724	A+
<b>TNWES 592x490x600</b>	592	490	600	ePM1-70%	10	2850	62	724	A+

Custom sizes on request.