

# RP55, RP65, RP85

Self-supported synthetic bag filters, filter class ISO ePM10

## APPLICATIONS

- Filter for general use in air handling units for industrial, production and technical areas
- Pre-filters in air supply units in spray booths

## ADVANTAGES

- Self-supported welded pockets
- Excellent dust holding capacity
- Progressive structure of the filter medium
- 100% combustible
- Low energy and maintenance costs

## FEATURES

- Medium: Synthetic with progressive structure
- Frame: Metal free
- Recommended final resistance: 250Pa
- Max. continuous temperature: 70 °C
- Max. relative humidity: 100%



DESCRIPTION	WIDTH (A) MM	HEIGHT (B) MM	LENGTH (C) MM	NUMBER OF POCKETS	CLASS ISO 16890	CLASS EN779:2012	FLOW M3/H	ΔP INITIAL
<b>RP55 592x592x310</b>	592	592	310	6	ePM10-50%	M5	3400	65
<b>RP55 288x592x310</b>	288	592	310	3	ePM10-50%	M5	1700	65
<b>RP55 490x592x310</b>	490	592	310	5	ePM10-50%	M5	2850	65
<b>RP55 592x592x600</b>	592	592	600	6	ePM10-50%	M5	3400	45
<b>RP55 288x592x600</b>	288	592	600	3	ePM10-50%	M5	1700	45
<b>RP55 490x592x600</b>	490	592	600	5	ePM10-50%	M5	2850	45
<b>RP55 Plus 592x592x600</b>	592	592	600	6	ePM10-50%	M5	3400	45
<b>RP65 592x592x600</b>	592	592	600	8	ePM10-50%	M6	3400	58
<b>RP65 288x592x600</b>	288	592	600	4	ePM10-50%	M6	1700	58
<b>RP65 490x592x600</b>	490	592	600	6	ePM10-50%	M6	2850	58
<b>RP65 Plus 592x592x600</b>	592	592	600	8	ePM10-50%	M6	3400	54
<b>RP85 592x592x600</b>	592	592	600	8	ePM10-50%	F7	3400	90
<b>RP85 288x592x600</b>	288	592	600	4	ePM10-50%	F7	1750	90
<b>RP85 490x592x600</b>	490	592	600	6	ePM10-50%	F7	2850	90
<b>RP85 Plus 592x592x600</b>	592	592	600	8	ePM10-50%	F7	3400	122